



DELTA ANTI SLIP FLOOR TREATMENT

Anti Slip Floor Treatment



DESCRIPTION

Delta Anti Slip Floor Treatment is a clear liquid that when applied to mineral floor surfaces, will create microscopic channels that enhance the anti slip performance of the floor. It is especially formulated for quick and easy application.

BENEFITS

- ❖ Improves slip resistance
- ❖ No irritating odour
- ❖ Non-flammable
- ❖ Easy to apply
- ❖ Fast drying, minimal shutdown during application
- ❖ Can be used indoors and outdoors
- ❖ **HACCP certified to Singapore Standard** for use in facilities covered by HACCP accreditation.

USES

- ❖ For use on mineral surfaces e.g. ceramic tiles, quarry tiles, mosaic, granite, marble, limestone, homogeneous tiles, glazed tiles, porcelain tiles, slate, terrazzo, concrete floor surfaces.
- ❖ Pool decks, kitchen, toilets, balconies, walkways, wet areas

TECHNICAL AND APPLICATION DATA

| SS485: 2011 | |
|-----------------|----------------------------|
| Slip Resistance | Dry: Classification F |
| | Wet: Classification X to V |

Note: Meets HDB's slip resistance specification under Standard Specifications for Building Works and Other Installations 2011.

HDB: Housing and Development Board of Singapore

| Slip Meter | |
|----------------------------------------------|-----------------|
| Slip Resistance (Coefficient of friction) | Dry: 0.6 – 0.75 |
| | Wet: 0.5 – 0.6 |

Note: Meets BCA's Acceptable Slip Resistance Grading: Surfaces with coefficient of friction below 0.4 are below acceptable safety limits according to BCA Accessibility Code 2013.

BCA: Building and Construction Authority of Singapore

COLOR

Clear colourless liquid

PACKAGING

500 ml



Delta Intercontinental Pte Ltd
38 Woodlands Industrial Park E1, #06-04
Singapore 757700

Tel : +65 6219 0700 Fax: +65 6219 2822
Email : deltaintercon@singnet.com.sg
Website : www.deltaintercon.com.sg



DELTA ANTI SLIP FLOOR TREATMENT

Anti Slip Floor Treatment

APPLICATION

- Apply Delta Anti Slip Floor Treatment on the surfaces by scrubbing with bristle pad or bristle brush for 2-3 minutes at coverage 10m²/lit.
- Rinse thoroughly with plenty of water and squeegee dry the floor.

Note: Subject to substrate, repeat the application steps if required.



STORAGE CONDITIONS AND SHELF LIFE

Delta Anti Slip Floor Treatment has a shelf life of 36 months in original unopened packing, stored in dry enclosed space without exposure to direct sunlight and extreme temperature. Protect from frost.

SAFETY

Delta Anti Slip Floor Treatment is highly corrosive and contact with skin and eyes must be avoided. Protective rubber hand gloves, rubber boots and eye shield should be worn during application. Full guidance on handling and disposal of this product is provided in a separate MSDS.

Delta Intercontinental Pte Ltd
38 Woodlands Industrial Park E1, #06-04
Singapore 757700

Tel : +65 6219 0700 Fax: +65 6219 2822
Email : deltaintercon@singnet.com.sg
Website : www.deltaintercon.com.sg