



DELTA REINFORCEMENT FABRIC

High Strength Non Woven Reinforcement Fabric



DESCRIPTION

A high strength non woven reinforcement fabric for use with Delta waterproofing systems.

BENEFITS

- ❖ High strength.
- ❖ Use with most waterproofing systems; allowing for thicker application rates.
- ❖ Will not shrink or perish.
- ❖ Bridges cracks and gaps.

USES

- ❖ Areas where waterproofing and flashing systems are required.
- ❖ Typically used in flat roof waterproofing areas, flashings, parapet walls and sealing of joints, laps and roofing screw in corrugated roofs.

COLOR

White

FINISH

Not to be laid as final finish.

SURFACE PREPARATION

Ensure the surface is free of all laitance, grease, oil, fungal growth, or loose and flaking particles.

APPLICATION

- ❖ Apply Delta Waterproofing Systems.
- ❖ Embed 1 layer of Delta Reinforcement Fabric.
- ❖ Apply Delta Waterproofing Systems.

TECHNICAL AND APPLICATION DATA

Thickness	1 mm
Weight	100 g/m ²
Tensile Strength (EN ISO 10319)	6.5 kN/m
Tensile Elongation (EN ISO 10319)	55%
CBR Puncture Strength (EN ISO 12236)	1250 N

PACKAGING

150 m²/roll

MAINTENANCE

Avoid puncturing and tearing of Delta Reinforcement Fabric.

Delta Intercontinental Pte Ltd
38 Woodlands Industrial Park E1, #06-04
Singapore 757700

Tel : +65 6219 0700 Fax: +65 6219 2822
Email : deltaintercon@singnet.com.sg
Website : www.deltaintercon.com.sg

DELTA REINFORCEMENT FABRIC

High Strength Non Woven Reinforcement Fabric



STORAGE CONDITIONS AND SHELF LIFE

Stored in dry enclosed place without exposing to direct sunlight and at temperature between 15°C to 35°C, protected from frost.