



DELTA WOOD DECK VARNISH

Clear Varnish for Wood Deck

DESCRIPTION

Delta Wood Deck Varnish is formulated to provide ultimate protection for wood deck that are exposed to UV and weather elements as well as frequent wear and tear.

BENEFITS

- ❖ Low odour
- ❖ Scratch resistance
- ❖ UV protection
- ❖ Fast drying
- ❖ Good flexibility – withstand constant wood expansion and contraction to minimise defects like cracking.
- ❖ Water resistance – prevents moisture absorption for prolonged wood life.
- ❖ Heavy metals free

USES

- ❖ For use on solid timber and also engineered wood with original wood structure on surfaces (e.g. plywood & particleboard etc).
- ❖ Exterior wood decks.
- ❖ Interior wooden floors/parquet and all wood fixtures exposed to frequent touch/use.

COLOR

Clear.

SURFACE PREPARATION

Substrates to be coated must be structurally sound, clean and free from any contamination. Use mechanical stone grinding or other mechanical means to remove laitance. All residues must be removed by vacuum cleaning to provide a dry, dust free open textured surface. For other specific application, consult DELTA INTERCONTINENTAL P/L.

APPLICATION

- ❖ Sand the wood surface thoroughly with #600 grit sand paper and wipe the wood surface with a cloth dampened with thinner to remove the debris. Allow thinner to evaporate fully.
- ❖ Apply 1 coat of Delta Wood Deck Varnish.
- ❖ Repeat Step 1 before applying 2nd and 3rd coat of Delta Wood Deck Varnish.

Tools – Applied by brush or roller.

Recoating time – Interval between coats: 3 hours 40°C.
Max. recoating time: 24 hours 40°C.

TECHNICAL AND APPLICATION DATA

Volume Solids	38 ± 2%
Flash Point	46°C
Recommended DFT	25 – 35 microns per coat
No. of Coats	3
Touch Dry	1 hour @ 40°C 2 hour @ 23°C
Hard Dry	3 hour @ 40°C 4 hour @ 23°C

Delta Intercontinental Pte Ltd
38 Woodlands Industrial Park E1, #06-04
Singapore 757700

Tel : +65 6219 0700 Fax: +65 6219 2822
Email : deltaintercon@singnet.com.sg
Website : www.deltaintercon.com.sg



DELTA WOOD DECK VARNISH

Clear Varnish for Wood Deck

PACKAGING

500ml, 5 litre

STORAGE CONDITIONS AND SHELF LIFE

Delta Wood Deck Varnish has a shelf life of 12 months in original unopened packing, stored in dry enclosed space without exposure to direct sunlight and extreme temperature. Protect from frost.

SAFETY

Product is flammable. Do not smoke when working. Ensure adequate ventilation and avoid inhaling vapours when working. Always use with suitable personal protective equipment.