



DELTA REINFORCEMENT FABRIC

High Strength Non Woven Reinforcement Fabric



DESCRIPTION

A high strength non woven reinforcement fabric for use with Delta waterproofing systems.

BENEFITS

- ❖ High strength.
- ❖ Use with most waterproofing systems; allowing for thicker application rates.
- ❖ Will not shrink or perish.
- ❖ Bridges cracks and gaps.

USES

- ❖ Areas where waterproofing and flashing systems are required.
- ❖ Typically used in flat roof waterproofing areas, flashings, parapet walls and sealing of joints, laps and roofing screw in corrugated roofs.

COLOR

White

FINISH

Not to be laid as final finish.

SURFACE PREPARATION

Ensure the surface is free of all laitance, grease, oil, fungal growth, or loose and flaking particles.

APPLICATION

- ❖ Apply Delta Waterproofing Systems.
- ❖ Embed 1 layer of Delta Polyester Fabric.
- ❖ Apply Delta Waterproofing Systems.

TECHNICAL AND APPLICATION DATA

Weight	80 g/m ²
Wide Width Tensile Strength (ASTM D 4595)	6 kN/m
Elongation at Break (ASTM D 4632)	60%
Puncture Resistance (ASTM D 4833)	185 N
Thickness	0.8 – 1.2mm (finished with Delta Waterproofing Systems)

PACKAGING

150 m²/roll

MAINTENANCE

Avoid puncturing and tearing of Delta Reinforcement Fabric.

Delta Intercontinental Pte Ltd
 38 Woodlands Industrial Park E1, #06-04
 Singapore 757700

Tel : +65 6219 0700 Fax: +65 6219 2822
 Email : deltaintercon@singnet.com.sg
 Website : www.deltaintercon.com.sg

DELTA REINFORCEMENT FABRIC

High Strength Non Woven Reinforcement Fabric



STORAGE CONDITIONS AND SHELF LIFE

Delta Reinforcement Fabric has a shelf life of 24 months in original packing, stored in dry enclosed place without exposing to direct sunlight and at temperature between 15°C to 35°C, protected from frost.